



4-PORT / 8-PORT POF NETWORK SWITCH

DM-1004-C DM-1008-C
FAST ETHERNET

The future of networking is here

The DiMoto DM-1004-C and DM-1008-C are high-performance unmanaged commercial-grade Plastic Optical Fibre (POF) Network Switches.

The DM-1004-C and DM-1008-C have 4 and 8 plastic optical fibre ports respectively and permit comprehensive Ethernet over Plastic Optical Fibre (EoPOF) networks to be deployed.

The DM-1004-C and DM-1008-C devices feature the Optolock® POF connector for plugless termination and bare plastic optical fibre can simply be plugged into the compact and sturdy switches, with zero configuration, providing instant connection to an EoPOF network.

EoPOF Overview

Ethernet over Plastic Optical Fibre is a simple, secure and high performance alternative for industrial, commercial and residential networking applications, delivering 100Mbps at over 70 meters.

All Dimoto's products incorporate a plugless termination system, enabling bare POF to be cut to length on-site and securely terminated in seconds.

EoPOF is an ideal solution for new, retrofit and temporary installations. The ability to install alongside power and route inconspicuously significantly reduces deployment time and cost, while the do-it-yourself simplicity empowers end users to continue to expand and modify their networks.



DiMoto's POF Network Switch: DM-1008 (bottom) and DM-1004 (top).

PRODUCT FEATURES

- **Terminate in seconds:** POF can be cut to length on-site and terminated in seconds.
- **Space saving:** POF is one quarter of the size and one third of the weight of CAT5 - simplifying handling and ideal for congested ducts and cable trays.
- **Simple and safe:** RCLED light sources are certified eye safe and operation in the visible (red) region simplifies debugging and fault detection activities.
- **Data Integrity:** EoPOF is immune to the effects of electrical noise, ground potential variations and lightning induced voltage spikes on data lines.
- **Robust Design:** the sturdy metal case protects your media converter from the industrial environment.

**Ethernet over Plastic Optical Fibre:
See the world of networking in a whole new light.**

PRODUCT SPECIFICATIONS

Network Ports

DM-1004-C: 4 x 100BaseFX OptoLock® POF Ports
DM-1008-C: 8 x 100BaseFX OptoLock® POF Ports

Standards Compliance

IEEE 802.3u 100BASE-FX Fast Ethernet

Switch Specifications

Technology: Store and Forward
Frame Memory: 128KB
Address Table: 2048
Speed: Full wire speed on all ports simultaneously

Optical Specifications

Source Type: RCLED
Wavelength: 660 nm nominal (Red)
Max. Tx Output: -2.0dBm
Min. Tx Output: -8.5dBm
Min Rx Sensitivity: -24dBm
Max Rx Sensitivity: -28.0dBm
Min Optical Link Budget: 15.5dBm
Max Distance: 70m (recommended & dependent on fibre)

Environmental Specifications

Operating Temperature: 0 to 60°C (32 to 140°F)
Storage Temperature: -20 to 85°C (-4 to 185°F)
Operating Humidity: 5% - 90% RH non condensing

Mechanical Specifications

Casing: IP30 Metal Enclosure
Mounting: Optional DIN Rail Mount Kit
Dimensions: 130x75x30mm / 200x75x30mm
Weight: 310g / 460g

Power Specifications

Input Voltage: 12VDC
Input Current (@12VDC): 0.33A / 0.5A

Regulatory Approvals

Safety (LED Source): IEC/EN 60825-1
EMI, EMC: CE, FCC, C Tick

Warranty

5 Year (return to base)

Package Contents

1x POF Network Switch
1x 12VDC Power Adapter
1x Installation Guide
1x Warranty Card
1x POF Cutting Tool

DiMoto Related Products

DM-PCI: POF PCI Adapter
DM-USB: POF USB Adapter
DM-1001-C: POF Media Converter
DM-1002-C: POF Media Converter/Switch
DM-CUTTER: POF multipurpose cutting tool
Fibre Optic Cable

Order Information

DM-1004-C-OPT
DM-1008-C-OPT

Notes

SMI POF connectors available on request. Please contact sales for details and minimum order quantities.
Plug pack temperature range: 0 to 40°C (32 to 104°F)

Contact DiMoto

DiMoto Pty Ltd
7 Meljaren Place,
Buderim QLD 4556
Australia

Phone +61 7 3129 0238
Fax: +61 7 3102 8551
Email: info@dimoto.com.au
Web: www.dimoto.com.au



DiMoto Pty Ltd designs, develops and markets Ethernet over Plastic Optical Fibre (EoPOF) networking devices and solutions worldwide.

DiMoto is a member of the leading Plastic Optical Fibre body, the Plastic Optical Fibre Trade Organization (POFTO).

Optolock is a registered trademark of Firecomms Ltd.